



折畳架台仕様 (標準)

伸縮架台仕様 (オプション)

定格荷重表

	R-37m	R-42m	R-46m	R-51m	R-55m	R-60m
3m	20.00	25.00	25.00	25.00	25.00	20.00
4m	20.00	25.00	25.00	25.00	25.00	20.00
5m	25.00	25.00	25.00	25.00	25.00	20.00
↓	↓	↓	↓	↓	↓	↓
25m	↓	↓	↓	↓	25.00	20.00
26m	↓	↓	↓	25.00	24.00	19.40
27m	↓	25.00	25.00	24.00	23.10	18.80
28m	25.00	24.50	24.00	23.10	22.10	18.20
29m	24.00	23.50	22.90	22.10	21.20	17.60
30m	22.90	22.50	21.90	21.20	20.30	17.00
31m	21.90	21.50	20.90	20.30	19.40	16.50
32m	21.00	20.50	20.00	19.40	18.50	15.90
33m	20.10	19.60	19.10	18.50	17.70	15.40
34m	19.30	18.80	18.20	17.70	16.90	14.90
35m	18.50	18.00	17.40	16.90	16.20	14.40
36m	17.80	17.30	16.70	16.20	15.40	13.90
37m	17.00	16.60	16.00	15.50	14.80	13.50
38m		15.90	15.40	14.90	14.10	13.00
39m		15.30	14.80	14.30	13.50	12.60
40m		14.70	14.30	13.70	13.00	12.20
41m		14.10	13.80	13.20	12.50	11.90
42m		13.50	13.30	12.70	12.00	11.50
43m			12.80	12.30	11.60	11.20
44m			12.40	11.90	11.20	10.80
45m			11.90	11.50	10.80	10.50
46m			11.50	11.10	10.50	10.20
47m				10.80	10.20	9.90
48m				10.50	9.90	9.60
49m				10.10	9.60	9.30
50m				9.80	9.30	9.00
51m				9.50	9.00	8.70
52m					8.80	8.50
53m					8.50	8.20
54m					8.30	8.00
55m					8.00	7.70
56m						7.50
57m						7.20
58m						7.00
59m						6.70
60m						6.50

仕様

商品コード		DL1 70000					
ジブ呼び		37m	42m	46m	51m	55m	60m
速度	巻上	ノッチ			5		
	荷重 (t)	1~4			25~2		
	速度 (m/min)	0~29			29~125		
	起伏 (s)	105	103	101	100	99	110
電源	旋回 (rpm)	0.5~0.6 (0.4:60mジブ15t以上)					
	電源	400V 50Hz (440V 60Hz)					
電動機	巻上	145kW 4P 40%ED インバータ制御					
	起伏	55kW 4P 25%ED インバータ制御					
	旋回	15kW 4P インバータ制御					
	昇降	22kW 6P 25%ED 油圧制御					
昇降	方式	油圧クライミング方式					
	ストローク	1.5m					
最大設置高さ (m)		295	290	285	200	100	

タワー
クレーン

製作物

荷 役

通信計測
機器

技術資料

資 料